

- LEGEND:**
- A. MINIMUM 6 INCHES
 - B. INLET PIPE INVERT TO BE 2-1/2 INCHES ABOVE LIQUID SURFACE
 - C. INLET PIPE TO TERMINATE 2/3 DEPTH OF WATER LEVEL
 - D. 90 DEGREE SWEEP, MINIMUM SIZE - 6 INCH SDR-26
 - E. 12 INCH FROM FLOOR TO END OF SWEEP
 - F. 12 INCH FROM FLOOR TO END OF OUTLET PIPE
 - G. MINIMUM DEPTH OF LIQUID CAPACITY - 42 INCHES
 - H. MAXIMUM DISTANCE FROM CEILING - 6 INCHES

- CAST IRON LIQUID TIGHT (GASKET) MANHOLE FRAME AND COVER TO GRADE
- NEENAH FOUNDRY R-1558 SYRACUSE CASTINGS 1012B OR APPROVED EQUAL

- RUBBER BOOT BY KOR-N-SEAL APPROVED EQUAL
- FILL VOID WITH NON-SHRINK WATER PROOF CEMENT GROUT



PRECAST CONCRETE GRAVITY GREASE INTERCEPTOR
 NOT TO SCALE

(BY FORT MILLER CO. OR EQUAL)

SARATOGA COUNTY SEWER DISTRICT #1 RESERVES THE RIGHT, AT OUR DISCRETION, TO CHANGE, MODIFY, ADD OR REMOVE PORTIONS OF THESE DETAIL SPECS AT ANY TIME

- NOTES:**
- CRUSHED STONE NOT TO EXCEED #2 IN SIZE
 - ALL PIPES AND FITTINGS SHALL BE 6 INCH SDR-26
 - SEWER LATERAL PIPE SHALL BE LAID AT A UNIFORM GRADE OF 1/4 INCH PER FOOT (ABOUT 2%) REFER TO SCD #1 "TRENCH DETAIL" FOR FURTHER INSTRUCTION
 - WOOD SHALL NOT BE USED
 - FRAME, GRADE RINGS (AS NEEDED), AND TANK SHALL BE LIQUID TIGHT AS A UNIT
 - SHALL BE VACUUMED OR WATER TESTED PRIOR TO BACKFILLING
 - WHERE INSTRUCTIONS ARE MANUFACTURER'S INSTRUCTIONS.
 - INSTALLED IN COMPLIANCE WITH ASME A
 - TANK SHALL INCORPORATE TWO (2) OR TWO (2) SIN
 - CAPACITY OF 750 GALLONS
 - EFFECTIVE CAPACITY OF
 - MULTIPLE CAPACITY GREASE INTERCEPTORS IN SE
 - REQUIRE EFFECTIVE CAPACITY IS GREATER THAN
 - BATTERED LOCATED AT THE AREA OF 50 INCHES
 - SHALL BE LOCATED AT THE AREA OF 50 INCHES
 - WATERLINE AREA OF 50 INCHES
 - MINIMUM AREA OF 50 INCHES
 - SHRINK WATER PROOF CEMENT GROUT

NOT FOR CONSTRUCTION

SARATOGA COUNTY SEWER DISTRICT #1

1002 HUDSON RIVER ROAD, MECHANICVILLE, NEW YORK

P.O. Box 550 Mechanicville, New York 12118
<http://www.saratogacountyny.gov/departments/sewer-district-1/>

Telephone: (518) 664-7396
 Fax: (518) 664-6280

